





Prices in Canadian Dollars. January 1, 2024

Custo	mer and Order Informati	0 n						
Custo	mer and Order Informati	OTI						
Purchase	Order *	Tag					v.0	0401
Dealer/Pr	ovider Name *							
Purchaser	Name and Contact Information *							
Shipping	Address *							
User Infor	mation (<i>if available</i>) Weight	lbs H	Height	_ft/in			* req	uired
Base C	Chair							
× 1501000	Fuze T50 50° Manual Tilt Wheelchair						ċ /	4,300
<u> </u>	Also available: the narrow Fuze T50n		air width of seat plus	only 4". See s	eparate order form.	pdgmobility.com/narrow	, -	+,300
_				,				
Frame	Type & Weight Capacity							
— 1500010	Fixed Width Frame Select a Fixed Seat V	Vidth below.						
☐ 1502010 ☐ 1502011	300 lbs Weight Capacity 400 lbs Weight Capacity Not compatible wi	th Transit Tie Down Sys	stem. Requires Flat-free Rea	r Tires or Heavy Du	ity Spoke Rear Wheels			
1502011	Adjustable Width Frame 250 lbs Weight			•		pelow	\$	100
	Taylor and the second s	ne capacity. Elimited co	impationity with rake Apart	Traine. Select air	rajustusie seut Widti	Sciow.	_	.00
Frame	Options							
1502222	Take-Apart Frame The Take-Apart frame	allows attendants to t	ake the Fuze apart in secon	ds without tools.	pdgmobility.com/take	e-apart	\$	500
	This feature reduces the weight of the heaviest pi Not compatible with Power Tilt, Drum Brakes, IV F							
	Take-Apart rear crossbar is not width adjustable.	DG will provide one no				ordered with		
	adjustable width frame (can be ordered with the	chair or later).						
	Fold &	TIL	+	Talca				
		1		IARO	55			
				apart				
		•	_					
	CUZETAL	ZE ADA	Check th	ne PDG Blog				
	FUZE IAK	(E-APA		re details.	B - C			
1502300	Transit Tie Down System (TTDS)							
	TTDS includes 4 factory-installed transport bracket Tested to max. Weight Capacity of 300 lbs.	ts. TTDS has been teste	ed according to ANSI/RESNA	WC 19. See Own	ers Manual for complete	e details.		
Seat V	Vidth			Overall chair w	idth is +7.5" for 12/16" I	RW and +8.5" for 20/22/24" RW		
_	Fixed Seat Widths Order with Fixed Fran			_				
1503015	_	1503016 16" Seat W		1503017	17" Seat Width			
1503018	_	1503019 19" Seat W		1503020	20" Seat Width			
1503021 1503023	<u> </u>	1503022 22" Seat W					\$	375
		justable Frame.	1441				7	3,3
1503113		1503114 13"-15" Rar	nge - Set at 14"	1503115	13"-15" Range - Se	t at 15"		
_	-			_	_			
1503215 1503218	_		nge - Set at 16" nge - Set at 19"	1503217 1503220	15"-20" Range - Se 15"-20" Range - Se			
		15 20 Hui	.5- 50:0:12		.5 20 hange 5c			







Seat [Depth					
	Standard Seat Depths (Adjustable)					
1504015	_	eat Depth	1504017	17" Seat Depth		
1504018	18" Seat Depth	eat Depth	1504020	20" Seat Depth		
	Custom Seat Depths Requires Stroller Handle Back - Str	aight. Not compatible with Reclining or	Fold-down Ba	ack.	\$	400
1504021	21" Seat Depth	eat Depth				
F	Calar					
Frame	: Color					
l_	PDG Premium Colors View color swatches on PDG's we	_	_			
1505001	Black Shimmer	_	1505016	Poppy Red		
1505003	·		1505011	Lollypop Red		
1505017		cal Teal	1505019	Tangerine Orange		
1505020			1505012 1505014	Bubble Gum Pink Daffodil Yellow		
1505022	,.	enberry Purple	1505014	Danodii Fellow	,	200
1505200	Custom Color Contact PDG for specifications.				\$	300
Armre	sts					
1506000	No Armrests					
	Height Adjustable Armrests (Single Post)				\$	295
1506114	10"-14" Range	6" Range			,	
1506100	Fixed Height Armrests (12") Full Length Armpad onl					
	Armrest Height If provided, Armrests will be set to this h		ting will be u	urad.		
		not include height of Armpad	iting will be t	iseu.		
	Armrest Position Indicate preference for Armrest position		usad			
4	In the interest of maintaining chair stabily and avoiding interferal			o accommodate stated preference.		
1506402	Mid	•				
	Locking Flip-up Armrests Not recommended for user	s with excessive strength or tone. Not co	mpatible wit	h Fold-down Back.	\$	295
1506310	Set at 10" □ 1506311 Set a	<u>_</u>	1506312			
1506313	Set at 13"	t 14"				
Armpa	a d s					
	Regular Armpads					
1507100	Desk Length - 2" x 10"	ength - 2" x 14"				
	Waterfall Armpads				\$	115
1507105	Desk Length - 2" x 10"	ength - 2" x 14"				
	Wide Armpads May interfere with wheels in some tilt cor	figurations.			\$	200
1507110	Desk Length - 3" x 10"	ength - 3" x 12"				
	Gel Armpads May interfere with wheels in some tilt config	urations.			\$	135
1507120	Full Length - 2" x 12"	ength - 3.5" x 12"				
	Contour Arm Trough with Hand Pad				\$	125
	Not compatible with Lap Tray, Locking Flip-up Armrests. May inte	_	ions.			
1507130	Right (4.5" x 18")	4.5" X 18")				
Armre	st Options					
		n each side. Seat size does not change.				
1507210	1" Total Additional Width	and the second s			\$	95
1507211	2" Total Additional Width				ċ	195







Seat P	an		
1508000	No Seat Pan		
1508001	Solid Aluminum Seat Pan	Ś	135

Seat Height Don't $\textbf{Select desired Seat-to-Floor Height} \quad \text{STF Height is adjustable within the range of the chosen Axle Plate (Low/Standard/High)}.$ forget 5" Casters 6" Casters & 6" Forks 13" 14" 15" 16" 17" 18" 19" RW 20" RW 14" 15" 16" 17" 12" 12" High STF High STF 16" 16" 20" 20" 22" Std. STF 22' Std. STF 24" Low STF 24" Low STF 6" Casters & 8" Forks 8" Casters & 8" Forks 16" 17" 16" 17" 13" 19" RW 20" RW 20" 12" High STF 12" High STF 16" 16" Std. STF 20" 20' 22" 22' Low STF 24" 24" Low STF Frog Legs 6" Soft Roll & Suspension Forks RW 13" 14" 15" 16" 17" 18" 19" 12" High STF 16" 20" 22" Std. STF 24" Low STF

Caster	· s				
	Urethane Casters				
1511051	5" x 1.25" Caster size	☐ 1511061 6" x 1.25" Caster size	1511081	8" x 1.25" Caster size	
1511063	6" x 1.50" Caster size				\$ 85
1511084	8" x 2.00" Caster size				\$ 135
	Pneumatic Casters				
1511161	6" x 1.25" Caster size				\$ 110
1511181	8" x 1.25" Caster size				\$ 120
1511184	8" x 2.00" Caster size				\$ 150
1511260	Frog Legs 6" x 1.50" Aluminu	m Soft-Roll Casters			\$ 275
1511400	Frog Legs Suspension Forks	Not compatible with 12" Rear Wheels. Requires 6"	Soft-Roll Caster.		\$ 595

Rear V	V h e e l s			
	Composite Wheels			
1512012	12" Wheel size	☐ 1512016 16" Wheel size	☐ 1512020 20" Wheel size	
1512022	22" Wheel size	☐ 1512024 24" Wheel size		
	Spoke Wheels			\$ 75
1512120	20" Wheel size	☐ 1512122 22" Wheel size	☐ 1512124 24" Wheel size	
1512224	24" Heavy Duty Spoke	Wheels		\$ 350
<i>\$</i>	Rear Wheel Position	Indicate Rear Wheel positioning preference. If left bla	ank, the default setting will be used.	
3	In the interest of maintaining cl	nair stabily and avoiding interferance with other cha	r functions, PDG may not be able to accommodate stated preference.	
1512401	Rear More stable	☐ 1512402 Mid	☐ 1512403 Front Less stable	







Axle T	y p e		
1513000	Quick Release Rear Axles		
1513010	Fixed Rear Axles		
			_
Rear T			
1514000	Urethane Tires		
1514010	Pneumatic Tires May result in a finished Seat Height 1/2" greater than stated.	\$	60
1514020	Pneumatic Tires with Flat-Free Inserts May result in a finished Seat Height 1/2" greater than stated. Not available with Spoke Wheels.	\$	95
Handr	İ m S Handrims are available only with 20", 22", and 24" Rear Wheels.		
☐ 1515000	No Handrims		
1515010	Standard Aluminum Handrims		
1515020	Plastic Coated Handrims Not compatible with Drum Brakes.	\$	150
1515030	Projection Handrims Composite Wheels only. 10 Projections, 30°, 1-1.8" Length.	\$	495
	Composite wheels only. 10 Projections, 30 , 1-1.6 Length.		495
Wheel	Locks & Brakes		
	User Wheel Locks		
1516010	Push to Lock		
1516030	Attendant Wheel Locks (Push to Lock) Not compatible with Drum Brakes, Wheel Lock Extensions.	\$	85
1516040	User & Attendant Wheel Locks Not compatible with Drum Brakes.	\$	125
1516005	Foot Operated Wheel Lock Rear-mounted unilateral single-activation lock. Not compatible with O2 Holder, IV Pole, Ventilator Tray, One-ArmDrive.	\$	595
1516300	Drum Brakes Available with 12" Composite or 20" Spoke Rear Wheels. Urethane Tires only.	\$	795
	12" Wheels compatible with 13", 14", 17.5", 18.5", 19.5" STF Height only. 20" Wheels compatible with 16", 17", 18" STF Height only.		
	User-activated Unilateral Wheel Lock Pull to Lock. Availlable up to 22" Seat Width only.	\$	795
1516310	Left Activation		
Wheel	Lock Options		
	Wheel Lock Extensions Not compatible with Attendant Wheel Lock.	\$	60
Anti-T	ippers		
1517010	Rear Anti-Tippers Required Safety Option.	\$	75
Back P	Posts		
Dack			
☐ 1518100	Back Post Style Stroller Handle Back This 1995 Canal Handle Back Not competible with Handle the Mounting District Property of the Competible William Competible Wil		
1518100	Stroller Handle Back		
1519300	Back Post Type Straight		ļ
1518200			
<u> </u>	Back Post Height Measured from the Seat Pan to the Handle. Short (17") 1518425 Tall (23")		
1310-20	Back Post Folding Fold-down Back is not compatible with Dynamic Rocker Back Interface, Reclining Backrest.		
<u> </u>	Fold-down		ļ
13.3223	Seat to Back Angle	—	
1519090	Set at 90°		
	Set at 114°		







Back	Options	
	Angle/Height Adjustable Stroller Handle Not compatible with Headrest Mounting Plate or Cane Handle Back.	\$ 150
1519010	Button on Outside 🔲 1519011 Button on Inside	
1519050	Removable Cane Handle Push Bar Not compatible with Stroller Handle Back.	\$ 140
	Endomorph Back Backrest will be narrower than Seat by total of 2x the Offset selected below. Minimum width of Backrest is 12".	\$ 395
1518102	1" Offset per side	
1519212	Headrest Mounting Plate Not compatible with Angle/Height Adjustable Stroller Handle, Cane Handle Back. Not required if mounting to a solid Back.	\$ 95
1519240	Seating Dynamics Dynamic Rocker Back Interface	\$ 2,995
	Not compatible with Take-Apart Frame, Fold-down Back, 30° Recline, Standard Upholstery. Only availabe with Stroller Handle - 8° Bend. Finished Back Post Height is 7" taller than selected Back Post Height. Maximim compative Seat Depth is 20". 90° and 98° Seat Angle only.	
Back	Upholstery	
1520000	No Back Upholstery	
	Standard Upholstery Not available with Cane Handle Back.	\$ 195
1520418	Short (18" Height) 🔲 1520421 Regular (21" Height)	
1520450	Tension Adjustable Upholstery Height of Upholstery is 16". Not available with Cane Handle Back.	\$ 295
	Position of Upholstery Select the desired position of the top of the Upholstery relative to the Seat Pan.	
	17" Back Post	
	Style 17" 18" 19" 20" 21" 22" 23" 24" 25" Style 17" 18" 19" 20" 21" 22" 23"	25"
	Short	
	Tension Adj	
Tilt A	ctivation	
	Attendant Tilt only Select trigger mounting location below.	
1523011	Right Back Post 🔲 1523012 Left Back Post	
	Power Tilt 40° tilt range. Includes 2 batteries for off-chair charging. pdgmobility.com/power-tilt	
1523400	Standard Power Tilt (250 lbs Weight Capacity)	\$ 1,795
1523401	Standard Power Tilt (350 lbs Weight Capacity) Requires Fixed Frame.	\$ 2,095
1523410	Power Tilt with Manual Tilt Override (250 lbs Weight Capacity) Allows for instant manual release of tilt in case of power tilt failure.	\$ 2,295
1523411	Power Tilt with Manual Tilt Override (350 lbs Weight Capacity) Allows for instant manual release of tilt in case of power tilt failure.	\$ 2,595
Coloct	Toggle Switch	
Select Control	button 5witch 1525451 Installed on right side 1525452 Installed on tert side	
Switch	_	525
	Optional for Egg Switch: Li 1523445 Swing Away Mounting Hardware Not compatible with all Headrest makes and models.	\$ 625
	Specify Headrest to be used: Tilt Limit Optional. If no tilt limit is selected, the full tilt range will be available.	
1523220	Tilt Limit Optional. If no tilt limit is selected, the full tilt range will be available. Set at 20°	
Reclir	n e	
1523310	Reclining Backrest (Manual)	\$ 895
	30° maximum recline. Not compatible with Cane Handle Back, Fold-down Back. Not available with 22″ Seat Depth. Finished Back Post Height is 3″ taller than selected Back Post Height.	
	Fillished back Post neight is 3 - taller than selected back rost neight.	
Front	Rigging	
1525000	No Front Rigging 🔲 1525001 Sector Blocks only	
	Easy-Out TM Front Rigging Effortless insertion and removal. No Hanger Bracket remains on frame. pdgmobility.com/easy-out	
1525410	Fixed 70°	\$ 95
1525420	Universal Angle Adjustable (0°-110°) Set at angle: (use increments of 10°)	\$ 295
	Adjust angle by loosening one bolt. Tool-free leg-length adjustment. Front Rigging can interfere with casters in the 90-110° settings.	

See next page for more options >







	Swing Away Front Rigging Legacy Design. Not compatible with Easy-Out. Requires pre-tilt of 5°.		
1525130	Swing Away 60°		
1525160	Swing Away 90° Includes 11"-16" Extension Tubes. Not compatible with 8" Casters.	\$	75
1525200	Swing Away Elevating Legrests Includes Calf Pads.	\$	375
1525300	1" Offset Hangers for Swing Away	\$	75
1525110	Standard Plug In 70° Front Rigging Legacy Design. Not compatible with Easy-Out.		
Footp	lates		
1526010	Composite Footplates		
1526020	Aluminum Angle Adjustable Footplates	\$	165
1526030	One Piece Fixed Footplate Available on Plug In Front Rigging only. Requires selection of Composite or Aluminum Angle Adjustable.	\$	350
1526040	One Piece Flip-up Footplate Requires selection of Composite or Aluminum Angle Adjustable.	\$	395
1526050	Interlocking Angle Adjustable Footplates Available for Seat Widths up to 21" only.	\$	195
Footre	est/Legrest Accessories		
	Calf Pad Not compatible with Gel Padding.		
1527012	For Easy-Out TM Front Rigging Includes reinforced premium Calf Pad mount.	\$	200
1527010	For Swing Away Front Rigging	\$	135
1527020	Gel Padding Not compatible with Calf Pad or Easy-Out Front Rigging.	\$	125
	Gel Knee Pad		
1527032	For Easy-Out TM Angle Adjustable Front Rigging	\$	200
1527032	For Swing Away ELR Front Rigging	\$	100
1527040	Length Adjustable Heel Loops	\$	50
1527040		\$	
	Bodypoint Padded Calf Strap Sizes greater than 22" are not padded.	ş	195
Front	Rigging Extension Tubes		
	Regular Extension Tubes No selection required for 90° Front Rigging		
_	Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging		
1528010	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging	Ś	75
_	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging	\$	75
1528010	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used.	\$	75
1528010	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used.	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	\$	75
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. I a neous Options		
1528010 1528020	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. I an e ous Options One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively.		3,500
☐ 1528010 ☐ 1528020 Misce	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. I an e o u s O p t i o n s One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires.		
☐ 1528010 ☐ 1528020 Misce	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. If an e o u s Options One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side		
☐ 1528010 ☐ 1528020 Misce	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side Large Hand Setup 24" Rear Wheels with 22" Driving Handrim.	\$	3,500
☐ 1528010 ☐ 1528020 Misce ☐ 1530010 ☐ 1530012	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side Large Hand Setup 24" Rear Wheels with 22" Driving Handrim. Spoke Guards Available for 20"-24" Composite Rear Wheels. Made from durable and lightweight aluminum.		
☐ 1528010 ☐ 1528020 Misce	Short 14°-18° for Easy-Out Front Rigging 13°-17° for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22° and 24° Composite Rear Wheels. Minimum 17° STF and 18° STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 130011 Installed on Left side Large Hand Setup 24° Rear Wheels with 22° Driving Handrim. Spoke Guards Available for 20°-24° Composite Rear Wheels. Made from durable and lightweight aluminum. Black 1530021 Frame Color	\$	3,500
☐ 1528010 ☐ 1528020 Misce ☐ 1530010 ☐ 1530012 ☐ 1530020	Short 14*-18* for Easy-Out Front Rigging 13*-17* for Swing Away and Standard Plug In Front Rigging Long 18*-24* for Easy-Out Front Rigging 15*-19* for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22* and 24* Composite Rear Wheels. Minimum 17* STF and 18* STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side Is30011 Installed on Left side Large Hand Setup 24* Rear Wheels with 22* Driving Handrim. Spoke Guards Available for 20*-24* Composite Rear Wheels. Made from durable and lightweight aluminum. Spoke Flip Down Abductor Requires Solid Seat Pan.	\$	3,500
☐ 1528010 ☐ 1528020 Misce ☐ 1530010 ☐ 1530012	Short 14°-18° for Easy-Out Front Rigging 13°-17° for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22° and 24° Composite Rear Wheels. Minimum 17° STF and 18° STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 130011 Installed on Left side Large Hand Setup 24° Rear Wheels with 22° Driving Handrim. Spoke Guards Available for 20°-24° Composite Rear Wheels. Made from durable and lightweight aluminum. Black 1530021 Frame Color	\$	3,500

See next page for more options >



Order Notes

FUZE T50

Order Form - Canada

Prices in Canadian Dollars. January 1, 2024

Gel Hip Guides Reduces available Seat Width by 2".	\$	495
Hip Belt Mount Provides improved mounting options for Bodypoint Hip Belt or other third-party belts.	\$	55
IV Pole	\$	295
Installed on Left Side 🔲 1530111 Installed on Right Side		
O2 Holder May add to overall width of the Chair.	\$	395
Ventilator Tray Reduces ground clearance. Chair may be unstable when unoccupied. Minimum Seat Width is 16".	\$	295
Not compatible with O2 Holder, Power Tilt, Foot Operated Wheel Locks.		
Ventilator Bracket Compatible with LTV1 (laptop) ventilator.	\$	295
Clear Lap Tray (Slide On) Available for Seat Widths of 17"-22" only. Not compatible with Contour Arm Trough.	\$	490
Q'Straint Lap Belt Model S5-6329-11. For use with WC-19 Transit Tie Down System. 24"-51" Belt Length.	\$	245
Wheelchair Backpack Black with PDG Logo. 17"x14" size.	\$	145
Adhesive Back Hook Strip, 2" x 30" For Cushion mounting.	\$	10
air Seating & Positioning		
Refer to the separate Seating & Positioning order form for PDG's on-chair options. Standard PDG discounts apply. pdgmobilty.com/seating		
	Hip Belt Mount Provides improved mounting options for Bodypoint Hip Belt or other third-party belts. IV Pole Installed on Left Side	Hip Belt Mount Provides improved mounting options for Bodypoint Hip Belt or other third-party belts. Variable State 1530111 Installed on Right Side Position of the Chair. State State

Please send your completed order form by email to info@pdgmobility.com or by fax to 877 323 9093.