






C	ustor	mer and Order In	formation							
Pı	urchase (Order *		Tag					v.(0401
D	ealer/Pro	ovider Name *								ļ
Pı	urchaser	r Name and Contact Informa	ition *							
Sł	nipping .	Address *								
U	ser Infor	rmation (<i>if available</i>) We	eight	_ lbs Height	ft/ir	n			* red	quired
В	ase C									
×	1501000	Fuze T50 50° Manual Tilt	Wheelchair					E1161	\$:	3,150
	(i)	Also available: the narrow	Fuze T50n with an	overall chair width of	seat plus only	4". See s	separate order form. <u>pdgmob</u>	bility.com/narrow		
F	r a m e	Type & Weight C	apacity							
		Fixed Width Frame Select	t a Fixed Seat Width belo	ow.						
	1502010	300 lbs Weight Capacity								
	1502011	400 lbs Weight Capacity Not	compatible with Transit	Tie Down System. Requires F	lat-free Rear Tires	or Heavy Di	uty Spoke Rear Wheels.			
	1502025	Adjustable Width Frame	250 lbs Weight Capacit	ty. Limited compatibility with	n Take-Apart Fram	e. Select an	Adjustable Seat Width below.		\$	100
F	r a m e	Options								
_		Take-Apart Frame The Ta	les Amout from a allows at	tondonts to take the Fuzz on	ort in seconds with	hout tools	ndamahilitu sam/taka anart		\$	500
_	1502222	This feature reduces the weight of Not compatible with Power Tilt, Dr Take-Apart rear crossbar is not wid adjustable width frame (can be orc	the heaviest piece of the rum Brakes, IV Pole, O2 Ho Ith adjustable. PDG will pi	e wheelchair to 29 lbs or less. older, Ventilator Tray, Ventila rovide one no-charge crossb	Perfect for transpo ator Battery Tray, D	orting it in th DRB, 13" STF.	he trunk of a car or SUV.	th	*	
		FUZE	TAKE-	Tilt APART	Check the PDG for more de					
	1502300	Transit Tie Down System TTDS includes 4 factory-installed tr		has been tested according to	ANSI/RESNA WC 1	9. See Own	ners Manual for complete details.			
		Tested to max. Weight Capacity of			71104,110		Craffic Company			
S	eat W	Vidth			Ove	erall chair w	vidth is +7.5" for 12/16" RW and +8.	.5" for 20/22/24" RW		
		Fixed Seat Widths Order	with Fixed Frame.							
	1503015	15" Seat Width	1503016	16" Seat Width		1503017	17" Seat Width			
	1503018	18" Seat Width	1503019	19" Seat Width						
	1503020	20" Seat Width	1503021	21" Seat Width		1503022	22" Seat Width	E2201	\$	375
	1503023	23" Seat Width						E2201	\$	375
	1503024	24" Seat Width						E2202	\$	575
		Adjustable Seat Widths	Order with Adjustable F	rame.						
	1503113	13"-15" Range - Set at 13"	1503114	13"-15" Range - Set at 14	1" □	1503115	13"-15" Range - Set at 15"			
	1503215	15"-20" Range - Set at 15"	1503216	15"-20" Range - Set at 16	5" [1503217	15"-20" Range - Set at 17"			
	1503218	15"-20" Range - Set at 18"	1503219	15"-20" Range - Set at 19)"					
	1503220	15"-20" Range - Set at 20"						E2201	\$	375







Seat D	Pepth					
	Standard Seat Depths (Adjustable)					
1504015	15" Seat Depth 1504016	16" Seat Depth	☐ 1504017 17" Seat Depth			
1504018	18" Seat Depth 1504019	19" Seat Depth				
1504020	20" Seat Depth			E2203	\$	500
	Custom Seat Depths Requires Stroller Handle Back	k - Straight. Not compatible with Reclining o	or Fold-down Back.			
1504021	21" Seat Depth			E2203	\$	525
1504022	22" Seat Depth			E2204	\$	800
	·					
Frame	Color					
	PDG Premium Colors View color swatches on PDG	G's website. <u>pdgmobility.com/colors</u>				
1505001	Black Shimmer 1505015	Sky Blue	☐ 1505016 Poppy Red			
1505003	Fine Texture Black	Lollypop Blue	☐ 1505011 Lollypop Red			
1505017	Arctic Grey	Tropical Teal	☐ 1505019 Tangerine Orange			
1505020	Olive Green 1505021	Lush Lilac	☐ 1505012 Bubble Gum Pink			
1505022	Leaf Green 1505023	Boysenberry Purple	☐ 1505014 Daffodil Yellow			
1505200	Custom Color Contact PDG for specifications.				\$	300
Armre	sts					
1506000	No Armrests					
	Height Adjustable Armrests (Single Post)			E0973	\$	345
1506114	10"-14" Range	12"-16" Range				
1506100	Fixed Height Armrests (12") Full Length Armpa	nd only.				
£	Armrest Height If provided, Armrests will be set to t	this height by PDG. If left blank, the default s	setting will be used.			
3	Seat Pan to top of Armrest:	Does not include height of Armpad				
1	Armrest Position Indicate preference for Armrest po	osition. If left blank, the default setting will	be used.			
,	In the interest of maintaining chair stabily and avoiding inte					
1506402	Mid 1506403	Front				
	Locking Flip-up Armrests Not recommended for	r users with excessive strength or tone. Not	compatible with Fold-down Back.	E0973	\$	345
1506310	Set at 10" 1506311	Set at 11"	☐ 1506312 Set at 12"			
1506313	Set at 13" 1506314	Set at 14"				
Armpa	ı d s					
	Regular Armpads					
1507100	Desk Length - 2" x 10"	Full Length - 2" x 14"				
	Waterfall Armpads				\$	115
1507105	Desk Length - 2" x 10" 1507106	Full Length - 2" x 14"				
	Wide Armpads May interfere with wheels in some til	ilt configurations.			\$	200
1507110	Desk Length - 3" x 10" 1507111	Full Length - 3" x 12"				
	Gel Armpads May interfere with wheels in some tilt of	configurations.			\$	135
1507120	_	Full Length - 3.5" x 12"			•	
	Contour Arm Trough with Hand Pad			E2209	\$	125
	Not compatible with Lap Tray, Locking Flip-up Armrests. Ma	y interfere with wheels in some tilt configur	rations.		•	
1507130		Left (4.5" x 18")			_	
Δ						
Armre	st Options					
	Armrest Wideners Move Armrests outward by up t	to 1" on each side. Seat size does not change	е.			
1507210	1" Total Additional Width				\$	95
1507211	2" Total Additional Width				\$	195







☐ 1512401 Rear More stable

FUZE T50

101 6			
Seat	Pan		
150800			
150800			 4.55
	Solid Aluminum Seat Fam	E2231	\$ 165
Seat	Height		
Don't	Select desired Seat-to-Floor Height STF Height is adjustable within the range of the chosen Axle Plate (Low/Standard/High).		
forget			
	RW 13" 14" 15" 16" 17" 18" 19" 20" RW 13" 14" 15" 16" 17" 18" 19" 20"		
	12"		
	16"		
	20"		
	24" LowSTF		
	6" Casters & 8" Forks 8" Casters & 8" Forks RW 13" 14" 15" 16" 17" 18" 19" 20" RW 13" 14" 15" 16" 17" 18" 19" 20"		
	12" Std.STF		
	16"		
	20"		
	22"		
	Frog Legs 6" Soft Roll & Suspension Forks RW 13" 14" 15" 16" 17" 18" 19" 20"		
	12"		
	16"		
	20"		
	22"		
Cast	ers		
	Urethane Casters		
151105	51 5" x 1.25" Caster size		
151106	6" x 1.50" Caster size		\$ 85
151108	8" x 2.00" Caster size		\$ 135
	Pneumatic Casters		
151116		E2214 & E2215	\$ 110
151118		E2214 & E2215	\$ 120
151118		E2214 & E2215	\$ 150
151126			\$ 275
151140	Frog Legs Suspension Forks Not compatible with 12" Rear Wheels. Requires 6" Soft-Roll Caster.	E1015	\$ 595
Rear	Wheels		
	Composite Wheels		
151201	2 12" Wheel size		
151202	22 22" Wheel size		
	Spoke Wheels		\$ 75
151212	20 20" Wheel size		
151222	24" Heavy Duty Spoke Wheels		\$ 350
<u></u>	Rear Wheel Position Indicate Rear Wheel positioning preference. If left blank, the default setting will be used.		
1	In the interest of maintaining chair stabily and avoiding interferance with other chair functions, PDG may not be able to accommodate stated preference	<u>.</u>	

☐ 1512403 Front Less stable

☐ 1512402 Mid







Axle	Туре		
1513000	Quick Release Rear Axles		
1513010	Fixed Rear Axles		
Rear ⁻	Tiras		
□ 1514000			
1514010		\$	60
☐ 131 4 020	Pneumatic Tires with Flat-Free Inserts May result in a finished Seat Height 1/2" greater than stated. Not available with Spoke Wheels. E2211 & E2213	\$	95
Handı	rims Handrims are available only with 20", 22", and 24" Rear Wheels.		
1515000	No Handrims		
1515010	Standard Aluminum Handrims		
1515020	Plastic Coated Handrims Not compatible with Drum Brakes.	\$	150
1515030	Projection Handrims Composite Wheels only. 10 Projections, 30°, 1-1.8" Length.	\$	495
Whee	l Locks & Brakes		
	User Wheel Locks		
1516010	_		
1516030		\$	85
1516040		\$	125
1516005		\$	595
		\$	795
	12" Wheels compatible with 13", 14", 17.5", 18.5", 19.5" STF Height only. 20" Wheels compatible with 16", 17", 18" STF Height only.		
	User-activated Unilateral Wheel Lock Pull to Lock. Availlable up to 22" Seat Width only.	\$	795
1516310	Left Activation		
Whee	l Lock Options		
	Wheel Lock Extensions Not compatible with Attendant Wheel Lock.	\$	80
	·	_	
Anti-	Tippers		
1517010	Rear Anti-Tippers Required Safety Option. E0971	\$	125
Back	Posts		
	Back Post Style		
<u> </u>	· _		
	Back Post Type		
1518200			
	Back Post Height Measured from the Seat Pan to the Handle.		
1518420	Short (17")		
r	Back Post Folding Fold-down Back is not compatible with Dynamic Rocker Back Interface, Reclining Backrest.		
1519220	Fold-down		
l _	Seat to Back Angle		
1519090			
1519108	3 Set at 114° □ 1519114 Set at 122°		







Вас	ck C	Options		
		Angle/Height Adjustable Stroller Handle Not compatible with Headrest Mounting Plate or Cane Handle Back.	\$	150
<u> </u>	19010	Button on Outside 🔲 1519011 Button on Inside		
<u> </u>	19050	Removable Cane Handle Push Bar Not compatible with Stroller Handle Back.	\$	140
		Endomorph Back Backrest will be narrower than Seat by total of 2x the Offset selected below. Minimum width of Backrest is 12".	\$	395
<u> </u>	18102	1" Offset per side		
<u> </u>	19212	Headrest Mounting Plate Not compatible with Angle/Height Adjustable Stroller Handle, Cane Handle Back. Not required if mounting to a solid Back.	\$	95
<u> </u>	19240	Seating Dynamics Dynamic Rocker Back Interface E2398	\$	2,995
		Not compatible with Take-Apart Frame, Fold-down Back, 30° Recline, Standard Upholstery. Only availabe with Stroller Handle - 8° Bend.		
		Finished Back Post Height is 7" taller than selected Back Post Height. Maximim compative Seat Depth is 20". 90° and 98° Seat Angle only.		
Вас	k U	Jpholstery		
<u> </u>	20000	No Back Upholstery		
		Standard Upholstery Not available with Cane Handle Back. E2611/E2612	\$	195
<u> </u>	20418	Short (18" Height) 1520421 Regular (21" Height)	•	.,,,
=	20450	Tension Adjustable Upholstery Height of Upholstery is 16". Not available with Cane Handle Back.	\$	295
			_	
		Position of Upholstery Select the desired position of the top of the Upholstery relative to the Seat Pan.		_
		17" Back Post 23" Back Post Style 17" 18" 19" 20" 21" 22" 23" 24" 25" Style 17" 18" 19" 20" 21" 22" 23" 24	, ,	25"
		Style 17" 18" 19" 20" 21" 22" 23" 24" 25" Style 17" 18" 19" 20" 21" 22" 23" 24" Short		:5
		Regular		
		Tension Adj		
			_	
Tili	t Ac	ctivation		
		Attendant Tilt only Select trigger mounting location below.		
<u> </u>	23011	Right Back Post		
		Power Tilt 40° tilt range. Includes 2 batteries for off-chair charging. pdgmobility.com/power-tilt E1002		
<u> </u>	23400	Standard Power Tilt (250 lbs Weight Capacity)	\$	2,295
152	23401	Standard Power Tilt (350 lbs Weight Capacity) Requires Fixed Frame.	\$	2,595
	23410	Power Tilt with Manual Tilt Override (250 lbs Weight Capacity) Allows for instant manual release of tilt in case of power tilt failure.		2,795
152	23411	Power Tilt with Manual Tilt Override (350 lbs Weight Capacity) Allows for instant manual release of tilt in case of power tilt failure.	\$	3,095
		Toggle Switch		
	Select ontrol	Button Switch		
S	witch	Stealth Egg Switch 1523440 Not installed		
		Optional for Egg Switch: U 1523445 Swing Away Mounting Hardware Not compatible with all Headrest makes and models. E1028	\$	625
		Specify Headrest to be used:		
		Tilt Limit Optional. If no tilt limit is selected, the full tilt range will be available.		
152	23220	Set at 20° 1523230 Set at 30° 1523240 Set at 40°		
Red	clin	e e		
<u> </u>	23310	Reclining Backrest (Manual) E1225	\$	895
		30° maximum recline. Not compatible with Cane Handle Back, Fold-down Back. Not available with 22" Seat Depth.	-	
		Finished Back Post Height is 3" taller than selected Back Post Height.		
Fro	nt	Rigging		
152		No Front Rigging 1525001 Sector Blocks only		
132	23000			
r.	25440	Easy-Out Front Rigging Effortless insertion and removal. No Hanger Bracket remains on frame. pdgmobility.com/easy-out	÷	0.5
	25410	Fixed 70° Universal Angle Adjustable (0° 110°)	\$	95
152	2J42U	Universal Angle Adjustable (0°-110°) Set at angle: (use increments of 10°) Adjust angle by loosening one bolt. Tool-free leg-length adjustment. Front Rigging can interfere with casters in the 90-110° settings.	\$	295

See next page for more options >








	Swing Away Front Rigging Legacy Design. Not compatible with Easy-Out. Requires pre-tilt of 5°.			
1525130	Swing Away 60°			
1525160	Swing Away 90° Includes 11"-16" Extension Tubes. Not compatible with 8" Casters.		\$	75
1525200	Swing Away Elevating Legrests Includes Calf Pads.	E0990	\$	415
1525300	1" Offset Hangers for Swing Away		\$	75
1525110				,,,
1323110	Standard Plug In 70° Front Rigging Legacy Design. Not compatible with Easy-Out.		—	
Footp	lates			
1526010	Composite Footplates			
1526020	Aluminum Angle Adjustable Footplates	K0040	\$	200
1526030	One Piece Fixed Footplate Available on Plug In Front Rigging only. Requires selection of Composite or Aluminum Angle Adjustable.		\$	350
1526040	One Piece Flip-up Footplate Requires selection of Composite or Aluminum Angle Adjustable.		\$	395
1526050	Interlocking Angle Adjustable Footplates Available for Seat Widths up to 21" only.	K0040	\$	200
Footr	est/Legrest Accessories			
	Calf Pad Not compatible with Gel Padding.			
1527012	For Easy-Out TM Front Rigging Includes reinforced premium Calf Pad mount.		\$	200
1527010			\$	135
1527020	Gel Padding Not compatible with Calf Pad or Easy-Out Front Rigging.		\$	125
	Gel Knee Pad			
1527032	For Easy-Out TM Angle Adjustable Front Rigging		\$	200
1527030	For Swing Away ELR Front Rigging		\$	100
1527030	Tor Swing Away Electronic nigging			100
1527040	Longth Adjustable Heal Loops	E0051	Ċ	50
1527040	Length Adjustable Heel Loops	E0951	\$	50
1527040 1527050	Length Adjustable Heel Loops Bodypoint Padded Calf Strap Sizes greater than 22" are not padded.	E0951 K0038	\$	50 195
1527050	Bodypoint Padded Calf Strap Sizes greater than 22" are not padded.			
1527050	Bodypoint Padded Calf Strap Sizes greater than 22" are not padded. Rigging Extension Tubes			
☐ 1527050	Bodypoint Padded Calf Strap Sizes greater than 22" are not padded. Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging			
☐ 1527050 Front ☐ 1528010	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging		\$	195
☐ 1527050	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging			
☐ 1527050 Front ☐ 1528010	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used.		\$	195
☐ 1527050 Front ☐ 1528010	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.		\$	195
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	K0038	\$	75
Front 1528010 1528020	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. Il a neous Options One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively.	K0038	\$	75
1527050 Front 1528010 1528020 Misce	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side	K0038	\$	75
1527050 Front 1528010 1528020 Misce	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side	K0038	\$	75
1527050 Front 1528010 1528020 Misce	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14°-18° for Easy-Out Front Rigging 13°-17" for Swing Away and Standard Plug In Front Rigging Long 18°-24° for Easy-Out Front Rigging 15°-19° for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side Large Hand Setup 24" Rear Wheels with 22" Driving Handrim. Spoke Guards Available for 20"-24" Composite Rear Wheels. Made from durable and lightweight aluminum.	K0038	\$	75
1527050 Front 1528010 1528020 Misce 1530010 1530012 1530012	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14°-18° for Easy-Out Front Rigging 13°-17° for Swing Away and Standard Plug In Front Rigging Long 18°-24° for Easy-Out Front Rigging 15°-19° for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22° and 24° Composite Rear Wheels. Minimum 17" STF and 18° STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side Large Hand Setup 24° Rear Wheels with 22° Triving Handrim. Spoke Guards Available for 20°-24° Composite Rear Wheels. Made from durable and lightweight aluminum. Black 1530021 Frame Color	K0038	\$	75
1527050 Front 1528010 1528020 Misce 1530010 1530012 1530012	Rigging Extension Tubes Regular Extension Tubes No selection required for 90° Front Rigging Short 14°-18° for Easy-Out Front Rigging 13°-17° for Swing Away and Standard Plug In Front Rigging Long 18°-24° for Easy-Out Front Rigging 15°-19° for Swing Away and Standard Plug In Front Rigging Lower Leg Length If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used. Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion. One-Arm Drive Available with 22° and 24° Composite Rear Wheels. Minimum 17" STF and 18° STF, respectively. Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires. Installed on Right side 1530011 Installed on Left side Large Hand Setup 24° Rear Wheels with 22° Driving Handrim. Spoke Guards Available for 20°-24° Composite Rear Wheels. Made from durable and lightweight aluminum. Black 1530021 Frame Color	K0038 E0958	\$ \$	195 75 3,500

See next page for more options >







1530080	Gel Hip Guides Reduces available Seat Width by 2".	E0956 & E1028	\$ 495
1530090	Hip Belt Mount Provides improved mounting options for Bodypoint Hip Belt or other third-party belts.	E1028	\$ 55
	IV Pole	E0776	\$ 295
1530110	Installed on Left Side		
1530120	O2 Holder May add to overall width of the Chair.	E2208	\$ 395
1530150	Ventilator Tray Reduces ground clearance. Chair may be unstable when unoccupied. Minimum Seat Width is 16".	E1029	\$ 295
	Not compatible with O2 Holder, Power Tilt, Foot Operated Wheel Locks.		
1530152	Ventilator Bracket Compatible with LTV1 (laptop) ventilator.	E1029	\$ 295
1530160	Clear Lap Tray (Slide On) Available for Seat Widths of 17"-22" only. Not compatible with Contour Arm Trough.	E0950	\$ 490
1530200	Q'Straint Lap Belt Model S5-6329-11. For use with WC-19 Transit Tie Down System. 24"-51" Belt Length.		\$ 245
1530222	Wheelchair Backpack Black with PDG Logo. 17"x14" size.		\$ 145
1530170	Adhesive Back Hook Strip, 2" x 30" For Cushion mounting.		\$ 10

On-Chair Seating & Positioning

Refer to the separate Seating & Positioning order form for PDG's on-chair options. Standard PDG discounts apply. pdgmobilty.com/seating

Order Notes

HCPCS codes provided are based on code verification by PDAC or PDG's interpretation of existing code definitions. Use of HCPCS codes does not guarantee coverage or payment.

Please send your completed order form by email to info@pdgmobility.com or by fax to 877 323 9093.